

# Solis-125K-EHV-5G

Solis Three Phase US Inverters



## Model:

**600V:** Solis-125K-EHV-5G

### Efficient

- Max. efficiency 99.1% (CEC efficiency 98.6%)
- > 150% DC/AC ratio
- Compatible with bifacial modules

### Safe

- Built-in PID recovery for better module performance (optional)
- Equipped with AC/DC switch, safe and convenient maintenance
- Globally recognised branded componentry for longer life

### Smart

- Strong reactive power compensation
- Multiple communication modes applicable to various scenarios
- Remote firmware upgrade with simple operation

### Economic

- Max. DC input voltage: 1500V
- Supports aluminium wire access to reduce cost

## Datasheet

Model Name		Solis-125K-EHV-5G
<b>Input DC</b>		
Max. input voltage		1500V
Rated voltage		950V
Start-up voltage		900V
MPPT voltage range		860-1450V
Max. input current		150A
Max. short circuit current		300A
MPPT number/Max. input strings number		1/20
<b>Output AC</b>		
Rated output power		125000W
Max. apparent output power		125000VA
Max. output power		125000W
Rated grid voltage		3Φ/PE, 600V
Rated grid frequency		60Hz
Max. output current		120.3A
Power Factor		>0.99 (0.8 leading - 0.8 lagging)
THDi		<3%
<b>Efficiency</b>		
Max. efficiency		99.1%
CEC efficiency		98.6%
<b>Protection</b>		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Surge protection		DC Type II / AC Type II
Grid monitoring		Yes
Anti-islanding protection		Yes
Temperature protection		Yes
Strings monitoring		Yes
I/V Curve scanning		Yes
Integrated DC switch		Yes
Integrated AC switch		Yes
<b>General Data</b>		
Dimensions (W*H*D)		46.3*28.1*12.4 in (1178*713.5*315 mm)
Weight		185.2 lbs (84 kgs)
Topology		Transformerless
Self consumption		<3W (night)
Relative humidity		0-100%
Operating ambient temperature range		-13°F to 140°F (-25°C to 60°C)
Storage environment		-13°F to 176°F (-25°C to 80°C)
Ingress protection		NEMA 4X
Cooling concept		Intelligent redundant fan-cooling
Max. operation altitude		13,120 ft (4000 m)
Compliance	UL 1741, UL 1741SA, UL 1998, UL 1699B, IEEE 1547, FCC Part 15 (Class A & B), CAN/CSA C22.2 107.1-1, Rule 21 phase I,II&III	
<b>Features</b>		
DC connection		MC4 connector
AC connection		OT terminal (max. 185 mm <sup>2</sup> )
Display		LCD
Communication	RS485, Optional: Wi-Fi, Cellular, Ethernet	