


HUMLESS POWER

5 kWh Lithium-Iron Phosphate (LiFePO4)

The Humless 5 kWh is ideal for residential, commercial, and emergency applications.

kWh	Cycle Life	Weight	Dimensions*
5.1	4,000+	106 lbs	17" x 16.625" x 8.75"



HUMLESS™

GENERAL SPECIFICATIONS

Nominal voltage	51.2 V
Voltage range	44 - 56.8 V
Capacity (Ah)	100 (Ah)
Continuous charging current	100 A
Continuous discharging current	100 A
Charge/discharge rate	1C
Peak current	120 A, ≤ 0.3s
Storage temperature	<86°F, SOC between 20%-60%
Output	Terminal lugs
Communication type	Double RS485
Protection function	Over-charge ; over-discharge ; over-current ; short circuit ; temperature protection

FEATURES & COMPLIANCE

Compatibility	All PV inverter manufacturers & grid-tied PV systems
Compliance	UL 1973, UL 1642, UN 38.3
Stacking	Up to 14 units in parallel

BATTERY AND VOLTAGE INFORMATION

Bulk	55.2 V
Absorb	55.2 V
Float	55 V
Low cut off	46 V
Absorb time	60 Minutes
Recharge	51 V
Battery activation	Press RST with pen or small screwdriver

MECHANICAL DATA

*Dimensions	17" x 16.625" x 8.75" (Handles included in dimension)
Handles	1.5" tall
Weight	106 lbs
Installation	Rack or Floor mounted
Cooling	Natural convection - no fan
Case material	Metal
Included	BMU/BMS/Modbus

BATTERY CHEMISTRY

Energy	5,120 Wh (100% DOD @ 0.2C Rate @ 77°F)
Chemistry	Lithium-Iron Phosphate (LiFePO4)
Cycle life	4000+ cycles (@0.2CA 80%DOD)
Temperature range	14°F to 113°F

WARRANTY

Limited warranty	10 years or 4000 cycles
------------------	-------------------------

