


LG NeON[®]R

LG370Q1C-V5

60

370W

LG NeON[®]R is LG's highest efficiency module in the market and provides world-class performance. The unique, back-contact cell structure eliminates electrodes on the front which maximizes the collection of light and improves overall reliability. LG NeON[®]R features an enhanced warranty, improved aesthetics on residential roof-tops, and the highest performance and durability under real-world conditions.



Features



Aesthetic Roof

LG NeON[®]R has been designed with aesthetics in mind: the lack of any electrodes on the front creates an improved, modern aesthetic.



Extended Product Warranty

LG has extended the product warranty of the NeON[®]R to 25 years, which is top level in the industry.



Better Performance on a Sunny Day

LG NeON[®]R now performs better on sunny days, thanks to its improved temperature coefficient.



Enhanced Performance Warranty

The LG NeON[®]R has an enhanced performance warranty. After 25 years, LG NeON[®]R is guaranteed at least 90.8% of initial performance.

When you go solar, ask for the brand you can trust: LG Solar

About LG Electronics

LG Electronics is a global leader in electronic products in the clean energy markets by offering solar PV panels and energy storage systems. The company first embarked on a solar energy source research program in 1985, supported by LG Group's vast experience in the semi-conductor, LCD, chemistry and materials industries. In 2010, LG Solar successfully released its first MonoX[®] series to the market, which is now available in 32 countries. The NeON[®] (previous MonoX[®] NeON), NeON[®]2, NeON[®]2 BiFacial won the "Intersolar AWARD" in 2013, 2015 and 2016, which demonstrates LG's leadership and innovation in the solar industry.

LG Solar

LG370Q1C-V5

General Data

Cell Properties (Material/Type)	Monocrystalline/N-type
Cell Maker	LG
Cell Configuration	60 Cells (6 x 10)
Module Dimensions (L x W x H)	1,700mm x 1,016mm x 40mm
Weight	17.5 kg
Glass (Thickness/Material)	2.8mm/Tempered Glass with AR Coating
Backsheet (Color)	White
Frame (Material)	Anodized Aluminium
Junction Box (Protection Degree)	IP68 with 3 Bypass Diodes
Cables (Length)	1,000mm x 2EA
Connector (Type/Maker)	MC 4/MC

Certifications and Warranty

Certifications	IEC 61215-1/-1-1/2:2016, IEC 61730-1/2:2016, UL 1703
	ISO 9001, ISO 14001, ISO 50001
	OHSAS 18001
Salt Mist Corrosion Test	IEC 61701:2012 Severity 6
Ammonia Corrosion Test	IEC 62716:2013
Module Fire Performance	Type 1
Fire Rating	Class C (UL 790)
Product Warranty	25 Years
Output Warranty of Pmax	Linear Warranty*

*Improved: 1st year 98%, from 2-24th year: 0.3%/year down, after 25th year: 90.8%

Temperature Characteristics


NMOT*	[°C]	44 ± 3
Pmax	[%/°C]	-0.30
Voc	[%/°C]	-0.24
Isc	[%/°C]	0.037

*NMOT (Nominal Module Operating Temperature): Irradiance 800 W/m², Ambient temperature 20 °C, Wind speed 1 m/s, Spectrum AM 1.5

Electrical Properties (NMOT)

Model	LG370Q1C-V5	
Maximum Power (Pmax)	[W]	279
MPP Voltage (Vmpp)	[V]	36.9
MPP Current (Impp)	[A]	7.55
Open Circuit Voltage (Voc)	[V]	40.3
Short Circuit Current (Isc)	[A]	8.71

I-V Curves



Electrical Properties (STC*)

Model	LG370Q1C-V5	
Maximum Power (Pmax)	[W]	370
MPP Voltage (Vmpp)	[V]	37.0
MPP Current (Impp)	[A]	10.01
Open Circuit Voltage (Voc, ± 5%)	[V]	42.8
Short Circuit Current (Isc, ± 5%)	[A]	10.82
Module Efficiency	[%]	21.4
Power Tolerance	[%]	0 ~ +3

*STC (Standard Test Condition): Irradiance 1000 W/m², Cell temperature 25 °C, AM 1.5

Operating Conditions

Operating Temperature	[°C]	-40 ~ +90
Maximum System Voltage	[V]	1,000
Maximum Series Fuse Rating	[A]	20
Mechanical Test Load (Front)	[Pa/psf]	5,400/113
Mechanical Test Load (Rear)	[Pa/psf]	4,000/83.5

*Test Load = Design x Safety Factor (1.5)

Packaging Configuration

Number of Modules per Pallet	[EA]	25
Number of Modules per 40ft HQ Container	[EA]	650
Packaging Box Dimensions (L x W x H)	[mm]	1,750 x 1,120 x 1,221
Packaging Box Gross Weight	[kg]	473

Dimensions (mm/inch)

