

Solis-(75-100)K-5G-US

Solis Three Phase US Inverters



Model:

- 480V:** Solis-75K-5G-US Solis-80K-5G-US
 Solis-90K-5G-US Solis-100K-5G-US

Ordering: Solis-(75-100)K-5G-US-AC

- SPRT (SunSpec MLRSD Transmitter)
- RSS (Tigo MLRSD Transmitter)
- PID (Potential Induced Degradation)

Efficient

- ▶ 8/9/10 MPPTs, max. efficiency 99% (CEC efficiency 98.5%)
- ▶ > 150% DC/AC ratio
- ▶ Compatible with bifacial modules

Safe

- ▶ IP66
- ▶ CA Rule 21 compliant and UL 1741 SA Certified
- ▶ Built-in PID recovery for better module performance (optional)
- ▶ Globally recognised branded component for longer life

Smart

- ▶ Intelligent string monitoring. Smart I-V curve scan
- ▶ Remote firmware upgrade with simple operation*

Economic

- ▶ Support "Y" type connection in DC side
- ▶ Support aluminium wire to reduce cost

Datasheet

Model Name	Solis-75K-5G-US	Solis-80K-5G-US	Solis-90K-5G-US	Solis-100K-5G-US
Input DC				
Max. input voltage			1000 V	
Rated voltage			600 V	
Start-up voltage			195 V	
MPPT voltage range			180-1000 V	
Max. input current	8*26 A	9*26 A		10*26 A
Max. short circuit current	8*40 A	9*40 A		10*40 A
MPPT number/Max. input strings number	8/16	9/18		10/20
Output AC				
Rated output power	75 kW	80 kW	90 kW	100 kW
Max. apparent output power	75 kVA	80 kVA	90 kVA	100 kVA
Max. output power	75 kW	80 kW	90 kW	100 kW
Rated grid voltage			3Φ/PE, 480 V	
Rated grid frequency			60 Hz	
Max. output current	90.2 A	96.2 A	108.3 A	120.3 A
Power Factor			>0.99 (0.8 leading - 0.8 lagging)	
THDi			<3%	
Efficiency				
Max. efficiency	98.7%			99.0%
CEC efficiency	98.3%			98.5%
Protection				
DC reverse-polarity protection		Yes		
Ground fault monitoring		Yes		
Anti-islanding protection		Yes		
Integrated AFCI (DC arc-fault circuit protection)		Yes		
Strings monitoring		Yes		
I/V Curve scanning		Yes		
Integrated PID recovery		Optional		
Rapid shutdown		Yes		
AC switch		Yes		
General Data				
Dimensions(W*H*D)		41.9*22.3*13.6 in (1065*567*344.5 mm)		
Weight		187 lbs (85 kgs)		
Topology		Transformerless		
Self consumption (night)		<2 W		
Relative humidity		0-100%		
Operating ambient temperature range		-13°F~140°F (-25°C~60°C)		
Storage environment		-40°F~176°F (-40°C~80°C)		
Ingress protection		TYPE 4X		
Cooling concept		Intelligent redundant fan-cooling		
Max. operation altitude		13,120 ft (4000 m)		
Compliance		UL 1741, IEEE 1547, UL 1699B, UL 1998, FCC, UL 1741SA, California Rule 21		
Features				
DC connection		MC4 connector		
AC connection		OT Terminal (max 350MCM)		
Display		LCD		
Communication		RS485, Ethernet, Optional: Wi-Fi, Cellular		

* Ordering guidelines: Ordering guidelines: Determine the basic model from above and add your desired features as described on PG1
Ex: Solis-75K-5G-US-AC-SPRT, (inverter with Sunspec MLRSD transmitter)