

MONO

**POLY**



**HELIENE**

**72<sup>P</sup>**

72-CELL POLYCRYSTALLINE MODULE



**330 Wp**

MAX POWER OUTPUT

**17.2%**

MAX EFFICIENCY

**10 YEAR**

PRODUCT WARRANTY

**25 YEAR**

LINEAR PERFORMANCE GUARANTEE



GUARANTEED POSITIVE POWER SORTING: [-0 : +4.99 WP]



AVAILABLE IN 1000V OR 1500V SYSTEM VOLTAGE RATING



MANUFACTURED ACCORDING TO INTERNATIONAL QUALITY SYSTEM STANDARDS: ISO9001



H-BLACK INTEGRATION AVAILABLE (ALL-BLACK MODULE)


HELIENE INC. IS A PREMIER SOLAR MODULE MANUFACTURER, SERVICING THE GROWING SOLAR ENERGY MARKETS OF NORTH AMERICA.

COMBINING PROVEN EUROPEAN TECHNOLOGY WITH NORTH AMERICAN INGENUITY ALLOWS HELIENE TO MAKE A REAL COMMITMENT IN PROVIDING SMARTER ENERGY CHOICES FOR THE FUTURE.


**Heliene Inc.**  
[www.heliene.com](http://www.heliene.com)

### LINEAR PERFORMANCE GUARANTEE



10 YEAR WORKMANSHIP WARRANTY • 25 YEAR LINEAR PERFORMANCE GUARANTEE



## DIMENSIONS FOR HELIENE 72P SERIES MODULES



## I-V CURVE FOR HELIENE 72P SERIES



## CERTIFICATIONS



## ELECTRICAL DATA (STC)

Peak Rated Power	$P_{mpp}$ (W)	330	325	320	315	310
Maximum Power Voltage	$V_{mpp}$ (V)	37.54	37.42	37.40	37.33	37.20
Maximum Power Current	$I_{mpp}$ (A)	8.85	8.745	8.64	8.50	8.40
Open Circuit Voltage	$V_{oc}$ (V)	46.26	46.11	45.96	45.81	45.66
Short Circuit Current	$I_{sc}$ (A)	9.13	9.05	8.97	8.89	8.81
Module Efficiency *	Eff (%)	16.8	16.5	16.8	16.5	16.2
Power Output Tolerance		[- 0, + 4.99] Wp				

STC - Standard Test Conditions: Irradiation 1000 W/m<sup>2</sup> - Air mass AM 1.5 - Cell temperature 25 °C

\* Calculated using maximum power based on full positive output tolerance [-0, +4.99] Wp

## MECHANICAL DATA

Dimensions (L x W x D)	1956 x 992 x 40 mm (77 x 39 x 1.6 inch)
Weight	23.6 kg (52.3 lbs)
Output Cables	1.1 m (43.3 inch) symmetrical cables with MC4 type connectors
Junction Box	IP-67 rated with bypass diodes
Frame	Double webbed 15 micron anodized aluminum alloy
Front Glass	Low-iron content, high-transmission PV solar glass
Solar Cells	72 Polycrystalline cells (156 x 156 mm)

## CERTIFICATIONS

UL Listed	ULC/ORD-C1703-1, UL1703, UL1703 Fire Classification Type 1
IEC Listed	IEC 61215, IEC 61730

All Heliene modules are certified under the California Energy Commission (CEC) Listing Report

## TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	+45°C (±2°C)
Temperature Coefficient of $P_{max}$	-0.43%/°C
Temperature Coefficient of $V_{oc}$	-0.32%/°C
Temperature Coefficient of $I_{sc}$	0.05%/°C

## MAXIMUM RATINGS

Operational Temperature	-40°C - +85°C
Max System Voltage	1000V / 1500V
Max Series Fuse Rating	15 A

## WARRANTY

10 Year Manufacturer's Workmanship Warranty

25 Year Linear Power Guarantee

(Refer to product warranty page for details)

## PACKAGING CONFIGURATION

Modules per box:	26 pieces
Modules per 53' trailer:	780 pieces